

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **FLEXY ANT. (Rosso, Grigio, Nero)**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Antifouling**

Identified Uses	Industrial	Professional	Consumer
Antifouling	-	✓	✓

1.3. Details of the supplier of the safety data sheet

Name	MARLIN SRL
Full address	Via Caduti sul Lavoro 4
District and Country	34015 Muggia (TS) Italia
	Tel. 040232588
	Fax 040232688
e-mail address of the competent person responsible for the Safety Data Sheet	information@marlinpaint.com

1.4. Emergency telephone number

For urgent inquiries refer to **+39 040 232588**

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Acute toxicity, category 4	H302	Harmful if swallowed.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Warning

Hazard statements:

- | | |
|-------------|---|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Precautionary statements:

- | | |
|------------------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P270 | Do not eat, drink or smoke when using this product. |
| P280 | Wear protective gloves / eye protection / face protection. |
| P301+P312 | IF SWALLOWED: call a POISON CENTER or doctor if you feel unwell. |
| P501 | Dispose of contents / container according to local legislation. |

Contains: DICOPPER OXIDE

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	
DICOPPER OXIDE		
CAS. 1317-39-1	25 - 50	Acute Tox. 4 H302, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10
EC. 215-270-7		
INDEX. 029-002-00-X		
2-METHOXY-1-METHYLETHYL ACETATE		
CAS. 108-65-6	25 - 50	Flam. Liq. 3 H226
EC. 203-603-9		
INDEX. 607-195-00-7		
1-METHOXY-2-PROPANOL		

 <p>MARLIN SRL <small>Via Carlo di Lorena 8/20015 Modigliana (MC) Italy Tel. +39 0543 220099 Fax. +39 0543 220099 Email: info@marlin.it P. IVA 01501070422 REG. IMP. TS N. 10401780422</small></p>	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 4/14

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

 MARLIN SRL <small> Via Carlo di Lorena 8/2001 - Modigliana (MC) - Italy Tel. +39 0733 920991 Fax +39 0733 920999 Email: info@marlin.it C.F. e P.IVA: 01509220542 COD. ABB: 15 - N. 15465788 - TS </small>	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 5/14

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

AUS	Österreich	Grenzwerteverordnung 2011 - GKV 2011
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
CYP	Κύπρος	Κ.Δ.Π. 268/2001; Κ.Δ.Π. 55/2004; Κ.Δ.Π. 295/2007; Κ.Δ.Π. 70/2012
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	275	50	550	100	SKIN.
VLEP	BEL	275	50	550	100	SKIN.
TLV	CYP	275	50	550	100	SKIN.
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN.
VLEP	FRA	275	50	550	100	SKIN.
WEL	GRB	274	50	548	100	
TLV	GRC	275	50	550	100	
OEL	IRL	275	50	550	100	SKIN.
TLV	ITA	275	50	550	100	SKIN.
OEL	EU	275	50	550	100	SKIN.

1-METHOXY-2-PROPANOL

Threshold Limit Value.

Type	Country	TWA/8h	STEL/15min
------	---------	--------	------------

		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	187	50	187	50	SKIN.
VLEP	BEL	375	100	568	150	SKIN.
TLV	CYP	375	100	538	150	SKIN.
AGW	DEU	370	100	740	200	
MAK	DEU	370	100	740	200	
VLA	ESP	375	100	568	150	SKIN.
VLEP	FRA	188	50	375	10	SKIN.
WEL	GRB	375	100	560	150	SKIN.
TLV	GRC	360	100	1080	300	
OEL	IRL	375	100	568	150	
TLV	ITA	375	100	568	150	SKIN.
OEL	EU	375	100	568	150	SKIN.
TLV-ACGIH		184	50	368	100	

ZINC OXIDE						
Threshold Limit Value.						
Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	5				
VLEP	BEL	10				
MAK	DEU	1		1		
VLA	ESP	2		10		
VLEP	FRA	5				
TLV	GRC	5		10		
OEL	IRL	2				RESP.
TLV-ACGIH		2		10		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 7/14

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	Not available.
Colour	Not available.
Odour	Not available.
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 32 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,15 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Solid content.	49,00 %
VOC (Directive 1999/13/EC) :	41,00 % - 758,50 g/litre.
VOC (volatile carbon) :	22,24 % - 411,43 g/litre.

 <p>MARLIN SRL <small>VIA CARLO AZEGLIO 8/20015 Modigliana (MC) Italy Tel. +39 0733 230991 Fax. +39 0733 230992 Email: info@marlin-srl.com P.I. e P.A. IVA: 01509020522 REG. IMP. TS N. 1040178052</small></p>	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 8/14

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL ACETATE: stable but with the air it may slowly develop peroxides that explode with an increase in temperature.

1-METHOXY-2-PROPANOL: absorbs and dissolves in water and in organic solvents, dissolves various plastic materials; it is stable but with air it may slowly form explosive peroxides.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

1-METHOXY-2-PROPANOL ACETATE: may react violently with oxidising agents and strong acids and alkaline metals.

1-METHOXY-2-PROPANOL: can react dangerously with strong oxidising agents and strong acids.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METHOXY-2-PROPANOL ACETATE: store in an inert atmosphere, sheltered from moisture because it hydrolyses easily.

1-METHOXY-2-PROPANOL: avoid exposure to the air.

10.5. Incompatible materials.

1-METHOXY-2-PROPANOL ACETATE: oxidising agents, strong acids and alkaline metals.

1-METHOXY-2-PROPANOL: oxidising agents, strong acids and alkaline metals.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

 <p>MARLIN SRL <small>VIA CADINI 41 - 41012 MANTOVA (MN) - ITALIA TEL. +39 0376 220991 Fax. +39 0376 220999 EMAIL: info@marlin.it C.F. e P.IVA: 01507920202 COD. FISC. 15/16 104078875</small></p>	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 9/14

Acute effects: ingestion of this product is harmful. Even small amounts of product may cause serious health problems (stomach pain, nausea, sickness, diarrhoea).

1-METHOXY-2-PROPANOL ACETATE: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

1-METHOXY-2-PROPANOL: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

TITANIUM DIOXIDE

LD50 (Oral).> 10000 mg/kg Rat

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral).8530 mg/kg Rat

LD50 (Dermal).> 5000 mg/kg Rat

1-METHOXY-2-PROPANOL

LD50 (Oral).5300 mg/kg Rat

LD50 (Dermal).13000 mg/kg Rabbit

LC50 (Inhalation).54,6 mg/l/4h Rat

SECTION 12. Ecological information.

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

DICOPPER OXIDE

LC50 - for Fish.	0,075 mg/l/96h Danio rerio
EC50 - for Crustacea.	0,042 mg/l/48h Daphnia similis
EC50 - for Algae / Aquatic Plants.	0,03 mg/l/72h Pseudokirchneriella subcapitata

ZINC OXIDE

LC50 - for Fish.	1,1 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea.	1,7 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants.	0,14 mg/l/72h Pseudokirchnerella subcapitata
Chronic NOEC for Fish.	0,53 mg/l
Chronic NOEC for Algae / Aquatic Plants.	0,024 mg/l

12.2. Persistence and degradability.

TITANIUM DIOXIDE

Solubility in water. < 0,001 mg/l

Biodegradability: Information not available.

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water. > 10000 mg/l
Rapidly biodegradable.

1-METHOXY-2-PROPANOL
Solubility in water. mg/l 1000 - 10000
Rapidly biodegradable.

DICOPPER OXIDE
Solubility in water. mg/l 0,1 - 100
Biodegradability: Information not available.

ZINC OXIDE
Solubility in water. 2,9 mg/l
Solubility in water. mg/l 0,1 - 100
Biodegradability: Information not available.

NOT rapidly biodegradable.

12.3. Bioaccumulative potential.

2-METHOXY-1-METHYLETHYL ACETATE
Partition coefficient: n-octanol/water. 1,2

1-METHOXY-2-PROPANOL
Partition coefficient: n-octanol/water. < 1

ZINC OXIDE
BCF. > 175

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
 Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
 Waste transportation may be subject to ADR restrictions.
CONTAMINATED PACKAGING
 Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name.

ADR / RID: PAINT or PAINT RELATED MATERIAL
 IMDG: PAINT or PAINT RELATED MATERIAL
 IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3
 IMDG: Class: 3 Label: 3
 IATA: Class: 3 Label: 3



14.4. Packing group.

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: 30 Limited Quantities 5 L Tunnel restriction code (D/E)

 MARLIN SRL <small>Via Carlo Azeglio 4, 10128 Biadene (Trento) (TN) Tel. +39 0461 860000 Fax. +39 0461 860001 Email: info@marlin.it P.I. e P. IVA: 01509020225 REG. IMP. TN N. 10401788 TN</small>	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 12/14

IMDG:	Special Provision: - EMS: F-E, S-E,	Limited Quantities 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 9i, 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

 <p>MARLIN SRL <small>Via Carlo di Lorena 8/2002 - Modigliana (MC) - Italy Tel. +39 0733 220991 Fax. +39 0733 220992 Email: info@marlinmanagement.com P.I. e P. IVA: 01509020262 REG. IMP. TS N. 10407188 TS</small></p>	MARLIN SRL	Revision nr. 2
	FLEXY ANT. (Rosso, Grigio, Nero)	Dated 04/06/2015 Printed on 24/06/2015 Page n. 13/14

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 453/2010 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament

 <p>MARLIN SRL <small>VIA SARDI 41 - 10045 SARDI (TO) - ITALIA TEL. +39 011 2309911 - FAX +39 011 2309920 EMAIL: info@marlin.it C.F. 01474150122 COD. FISC. 15161490122</small></p>	<p>MARLIN SRL</p> <hr/> <p>FLEXY ANT. (Rosso, Grigio, Nero)</p>	<p>Revision nr. 2</p> <p>Dated 04/06/2015 Printed on 24/06/2015</p> <p>Page n. 14/14</p>
---	---	---

- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 06 / 08 / 12 / 14.